

SWG-1016 Gateway



Parameter

- Dimension (without antenna) : 360*210*44.4
- Weight (without antenna) : 1.544kg
- CDMA Channel : 16
- Power: 36W
- LAN Port : 2
- USB Port : 2
- SIM Cards: Hot-Swap
- SIM6320C Module: 16
- Operation Temperature: 0°C ~ 40°C
- Operation Humidity Range: 10% ~ 90%
- Storage Temperature Range: -20°C ~ 70°C

CDMA Features

- CallerID Display&Hide
- CDMA : 800MHz
- Real Open API Protocol
- Call Duration Limitation
- SMSC/SMS/USSD
- PIN Identification
- Voice Codec
- Ports Group Management
- SMS Remotely Controlling Gateway
- SMS Bulk Transceiver, Sent to Email and Automatically Resend
- SMS Forwarding and Quick Reply

VoIP Characters

- Support SIP, IAX2 Protocol
- Add, Modify & Delete SIP/IAX2 Trunk
- SIP/IAX2 Registration with Domain
- DTMF Mode: RFC2833/Inband/SIPInfo
- Multiple SIP/IAX2 Registrations modes

SWG-1016 Gateway



Network

- IPv4, UDP/TCP, DHCP, TELNET, HTTP/HTTPS, TFTP
- HTTP/SSH (Optical Telnet)
- Ping & Traceroute Command on the Web
- Simple Security Strategy: white list, black list, security rules

System Features

- Abundant Codecs: G.711U, G.711A, GSM, G.722, G.723, G.726, G.729
- Simple and convenient configuration via Web GUI
- Firmware Update by HTTP
- Automatically Reboot
- Support DISA
- Multiple Detailed LOG Output
- Call Status Display
- Mobile number portability (MNP)
- CDR
- Support Configuration files backup and upload
- Support for Custom scripts, dialplans
- Restore Factory Settings

Contact Us: 10/F, Building 6-A, Baoneng Science and Technology Industrial Park, Longhua New District, Shenzhen, Guangdong, China 518109

Tel: +86-75566630978, 82535461, 82535362 Email: sales@openvox.cn support@openvox.cn