



OpenVox MAG1000 Series Analog Gateway

Overview

OpenVox MAG 1000 is a multifunctional analog gateway for seamless connection between IPPBX, fax machines, analog phones and operators. It provides three interfaces of RJ11/RJ45/RJ21, covering almost all the wiring needs of users in all scenarios. In addition, it has excellent full concurrent voice/ fax processing capabilities, strong performance and high stability, and provides high-quality call services for operators, enterprises, call centers and residential users in residential communities.

The MAG1000 Analog Gateways are developed for interconnecting a wide selection of codecs including G.711A, G.711U, G.729A, G.722, G.726, iLBC. MAG1000 series use standard SIP protocol and compatible with Leading VoIP platform, IPPBX and SIP servers, such as Asterisk, Issabel, 3CX, FreeSWITCH, BroadSoft and VOS VoIP operating platform.

Performance and Features

- 16/ 24/ 32 FXO/FXS ports
- Stable function, flexible dialplan and friendly Web GUI
- Strong security and high stability
- Designed for almost all kinds of users
- Fully Compatible with Leading SIP based VoIP Telephony System
- Support voice, fax and POS terminal access

System Features

- NTP time synchronization and client time synchronization
- Support modify username and password for web login
- Update firmware online, backup/restore configuration file
- Abundant Log Info, Automatically Reboot, Call status display
- Language selection (Chinese/English)
- Open API interface, support the secondary development of applications
- Support SSH remote operation and restore the factory settings

Telephony Features

- Support Volume adjustment, Gain adjustment, call transfer, call hold, call waiting, call forward, Caller ID display
- Three way calling, Call transfer, Dial-up matching table
- Support T.38 fax relay and T.30 fax transparent, FSK and DTMF signaling
- Support Ring cadence and frequency setting, WMI (Message Waiting Indicator)
- Support Echo cancellation, Jitter buffer
- Support customizable DISA and other applications

SIP Features

- Support add, modify & delete SIP Accounts, batch add, modify & delete SIP Accounts
- Support multiple SIP registrations : Anonymous, Endpoint registers with this gateway, This gateway registers with the endpoint
- SIP accounts can be registered to multiple servers

Network

- Network type: Static IP, Dynamic
- Support DDNS, DNS, DHCP, DTMF relay, NAT
- Telnet, HTTP, HTTPS, SSH, TFTP, FTP
- VPN clients: PPTP/OpenVPN/Zerotier/L2TP/N2N (Not available for Russia)
- Network Toolbox

Certification

- CE



Specifications

OpenVox MAG1000 Series Analog Gateway			
Product Name	MAG1000-16	MAG1000-24	MAG1000-32
Interfaces			
Ports	16 FXO/FXS ports	24 FXO/FXS ports	32 FXO/FXS ports
Port type	RJ11/RJ45/RJ21		
USB	RJ45		
Ethernet port	2 * 10/100Mbps ports		
General Info			
Dimension (bare)	440mm*45mm*220mm		
Dimension(with packaging)	510mm*90mm*310mm		
Weight(with packaging)	2.86kg	2.98kg	3.1kg
Max Power Consumption	20W	28W	36W
Power Supply	90-264VAC		
Operation Temperature	0°C ~ 45°C		
Operation Humidity Range	10% ~ 90% NON-CONDENSING		
Storage Temperature Range	-20°C ~ 70°C		
Short/Long Haul Ring Load	2 REN, up to 3km on 24AWG line		
Certification	CE		

Address: Room 624, 6/F, Tsinghua Information Port, Book Building, Qingxiang Road, Longhua Street, Longhua District, Shenzhen, Guangdong, China 518109

Tel: +86-755-66630978,82535461, 82535362

Business Contact: sales@openvox.cn Technical Support: support@openvox.cn Website: www.openvox.cn